



Chassis Brand
Emission Regulation
Max. Concrete Output (L/H)
Max. Concrete Pressure (L/H)
Max. Vertical Reach
Concrete Slump

SINOTRUK
Optional
180/122 m³/h
7/11 MPa
61.2 m
120-230 mm

CLG6264F

BOOM

PUMP

CLG6264F SPECIFICATIONS >>>

BOOM SPECIFICATIONS--Z FOLD DESIGN

Vertical reach	61.2 m
Horizontal reach	57.2 m
Reach depth	46 m
Unfolding height	13.2 m
Section articulation	90 ° / 180° /180° /230° / 180°/ 180°
Front outrigger spread	12.269 m
Rear outrigger spread	13.709 m
Slewing range	± 335°
End hose diameter	125 mm
End hose length	3 m
Boom control type	Radio Remote

PUMP SPECIFICATIONS

Concrete output (L/H)	180/122 m³/h
Concrete pressure (L/H)	7/11 MPa
Max. size aggregate	40 mm
Concrete cylinder bore	260 mm
Stroke length	1,900 mm
Hopper capacity	0.7 m³
Concrete valve type	S tube
Hydraulic system type	Open Loop
Hydraulic reservoir	740 L
Water tank	400 L

CHASSIS SPECIFICATIONS

Chassis	SINOTRUK
Driving type	8 x 4
Emission regulation	Optional

DIMENSION & MASS

Length	15,240 mm
Width	2,550 mm
Height	4,000 mm
Weight	44,000 kg

BUILT FOR EFFICIENCY

Computer-controlled power matching technology, optimizes match of power and operating conditions leading to a 10% decline in fuel consumption.

Big bore concrete cylinder and streamlined hopper maximize concrete feeding efficiency.

EASY TO MAINTAIN

Maintenance free hydraulic valves from Rexroth and Vickers, World class components used for key systems.

Block grease distributor ensures lubricating points get proper amount of grease.

Automatic piston retraction makes maintenance easy, convenient placement of key maintenance points.

ALWAYS RELIABLE

V-shaped waterproof hydraulic seals prevent the hydraulic oil from being emulsified.

OPERATOR SAFETY AND COMFORT

Remote, cable and Local control modes for convenience featuring emergency stop for greater safety.

Comprehensive error monitoring system with alerts to wireless remote for real-time monitoring.